

TRANSPONDER AND COMPONENTS



Door Reader DR-55x

- Door reader for access control
- housing white or black
- integrated Beeper
- 3 LED's (yellow, red, green)
- Interface CI20mA Wiegand, RS-232, RS-485, customised
- For inside- and outside applications
- Plug connection
- switch box mounting, wall mounting (adaptor)
- CE and radio approval

Technical Data:

| | |
|-------------------------|--|
| Dimensions (l x w x h): | (80x80x15) mm, with plug 20mm |
| Power supply: | 12V DC |
| Current consumption: | ca.100mA |
| Frequency: | 125 KHz , 13,56 MHz |
| Transponder: | EM V4x02, V4x50 Sokymat Titan, Unique, Nova, Q5 (unique mode) Philips Mifare |
| Antenna: | integrated Antenna |
| Interface: | Interface CI20mA Wiegand, RS-232, RS-485, customised |
| Housing: | Plastic, white, black |
| Operating: | -20°C .. +70°C 125 kHz -20°C .. +55°C 13,56 MHz (Mifare) |

Order-Information:

| | |
|---------|--|
| DR-55-1 | 4x02, V4x50, Titan, Unique, Nova, Q5 (unique mode) |
| DR-55-2 | Mifare |
| AP-55 | Adaptor, conic (80x80x25) mm, white, black |