

TRANSPONDER AND COMPONENTS



Desktop Reader DT-xxxx

- 125 kHz Reader / Writer
- Flash Software Update (ISP)
- LED's (red, green)
- Interface RS-232/RS-485/USB
- Output Relay
- integrated Antenna
- suitable for wall mounting (door reader)

Technical Data:

Dimensions (l x w x h):	(80 x 80 x 23) mm (120 x 120 x 23) mm (200 x 200 x 23) mm
Power supply:	8-12V DC or 8V AC (USB Version - Power supply not applicable)
Output-Relay	max. 1A
Frequency:	125 KHz
Transponder:	EM4102 EM4x50 Hitag 1 Hitag 2 Hitag S 256 / 2048 ATA 5567 /5577
Antenna:	integrated antenna
Interface:	RS-232 / RS-485 / USB
Reading distance:	up to 200 mm
Housing:	ABS plastic, IP55
Operating:	0°C .. +65°C

Order Information:

DT-0801	(80 x 80 x 23) mm, RS-232
DT-0803	(80 x 80 x 23) mm, RS-485
DT-0804	(80 x 80 x 23) mm, USB
DT-1201	(120 x 120 x 23) mm, RS-232
DT-1203	(120 x 120 x 23) mm, RS-485
DT-1204	(120 x 120 x 23) mm, USB
DT-2001	(200 x 200 x 23) mm, RS-232
DT-2003	(200 x 200 x 23) mm, RS-485
DT-2004	(200 x 200 x 23) mm, USB